

Calkins Field Cultivator

Clearance. Consistency. Flexibility.

Terrain is seldom uniform. That's why the new 5-bar Calkins Field Cultivator is designed to give you superior trash clearance, the ability to traverse rolling terrain and consistent depth control to handle uneven ground contours. Save time and fuel with features like:

- **5-bar frame trash clearance** - Shanks spaced out farther than the 4-bar version for better trash clearance.
- **Field-replaceable spindles**
- **28" clearance between shanks on any one bar.**
- **Shortened close-coupled tongue** -Reduces bridging and helps the cultivator follow the contour of hilly ground, avoiding ground gouge common with long tongue cultivators.
- **Adjustable shank** - Trip spring pressure can be adjusted from 90 lbs. to 225 lbs. to meet varying ground conditions.



Spring-Steel Shank Tandem Walking Beam

PRODUCT SPECIFICATIONS

3-Section and 5-Section Modes

WORKING WIDTH: 26' 10" to 44' 4" (3-sect) 45'6" to 58'4" (5-sect)

CENTER: 12'

WINGS: 7', 9' 6", 12' (3-section) 9' 6", 12' (5-section inner wings);
7' (5-section outer wings)

WING EXTENSIONS: 2 to 14 shanks

FRAME: 4" x 4" square steel tubing

FRAME DEPTH: 114"

TRANSPORT HEIGHT: 15'4"

TRANSPORT WIDTH: Adjustable to 17'3"

SHANK: 5/8" x 1-3/4" spring steel

SHANK SPACING: 7" or 9"

SHANK CLEARANCE: 24" frame to point